



ADDENDUM NUMBER: 004

**COUNTY OF MOORE
NEW RECREATION CENTER
CARTHAGE, NC**

**OWNER PROJECT NUMBER IFB-2019-04
PROJECT NUMBER 14558.00**

April 12, 2019

This Addendum issued prior to receipt of Bid hereby becomes a part of the Construction Documents for the above project.

All information contained in this Addendum supersedes and takes precedence over any conflicting information in the original Bidding Documents dated March 21, 2019.

CHANGES TO PROJECT MANUAL

SPECIFICATION SECTION 00 01 10 – TABLE OF CONTENTS

1. Delete section in its entirety and replace with the enclosed dated April 12, 2019.

SPECIFICATION SECTION 23 74 13 – PACKAGED ROOFTOP UNITS / OUTDOOR AIR HANDLING UNITS

1. Issued section in its entirety (9 pages) dated April 12, 2019.

CHANGES TO DRAWINGS

Not Applicable.

CLARIFICATIONS

Not Applicable.

ENCLOSURES:

SPECIFICATION SECTIONS

00 01 10 Table of Contents

23 74 13 Packaged Rooftop Units / Outdoor Air Handling Units

SHEETS / BULLETIN DRAWINGS

Not Applicable.

MISCELLANEOUS

Not Applicable.

6302 Fairview Road
Suite 102
Charlotte, NC 28210
www.clarkpatterson.com
704.331.9131 TEL
704.331.0402 FAX

TABLE OF CONTENTS

DIVISION 00 – PROCUREMENT AND CONTRACTING REQUIREMENTS

00 01 01	Title Page.....	00 01 01	1
00 01 10	Table of Contents	00 01 10	1-6
00 11 13	Advertisement for Bids.....	00 11 13	1-2
00 21 13	Instructions To Bidders	00 21 13	1-5
00 31 00	Available Project Information	00 31 00	1
00 31 26	Hazardous Materials Report	00 31 26	1-23
00 31 32	Geotechnical Data	00 31 32	1-47
00 41 00	Bid Form.....	00 41 00	1-5
00 50 00	Contracting Forms and Supplements.....	00 50 00	1-2
00 52 00	Agreement (AIA A101)	00 52 00	1
00 61 13	Contractor's Affidavit and Partial Release of Claims and Liens.....	00 61 13	1-2
00 61 16	Contractor's General Warranty.....	00 61 16	1
00 61 19	Asbestos-Free Warranty	00 61 19	1
00 62 13	Moore County E-Verify Affidavit.....	00 62 13	1
00 62 39	Identification of HUB Certified/Minority Business Participation.....	00 62 39	1-6
00 62 41	Non-Collusion Affidavit.....	00 62 41	1
00 62 45	County of Moore Vendor Application	00 62 45	1
00 62 51	Request for Taxpayer Identification Number and Certification (W9-2017)	00 62 51	1
00 72 00	General Conditions (AIA A201)	00 72 00	1-49

DIVISION 01 – GENERAL REQUIREMENTS

01 10 00	Summary	01 10 00	1
01 20 00	Price and Payment Procedures.....	01 20 00	1-3
01 22 00	Unit Prices	01 22 00	1-2
01 23 00	Alternates.....	01 23 00	1
01 25 00	Substitution Procedures	01 25 00	1-3
01 26 57	Pricing of Construction Contract Change Orders.....	01 26 57	1-6
01 30 00	Administrative Requirements	01 30 00	1-11
01 32 16	Construction Progress Schedule	01 32 16	1-2
01 40 00	Quality Requirements	01 40 00	1-4
01 41 00	Special Inspection Services	01 41 00	1-5
01 41 10	Statement of Special Inspections.....	01 41 10	1-8
01 50 00	Temporary Facilities and Controls	01 50 00	1-3
01 51 00	Temporary Utilities.....	01 51 00	1-2
01 57 13	Soil Erosion and Sediment Control	01 57 13	1-9
01 60 00	Product Requirements	01 60 00	1-3
01 70 00	Execution and Closeout Requirements.....	01 70 00	1-10
01 78 00	Closeout Submittals	01 78 00	1-5

DIVISION 02 – EXISTING CONDITIONS

02 41 16 Structure Demolition02 41 16 1-7

DIVISION 03 - CONCRETE

03 10 00 Concrete Forming and Accessories31 10 00 1-8
03 20 00 Concrete Reinforcing03 20 00 1-4
03 30 00 Cast-In-Place Concrete03 30 00 1-6
03 35 15 Polished Concrete Floor Finish03 35 15 1-5
03 45 00 Precast Architectural Concrete03 45 00 1-3

DIVISION 04 – MASONRY

04 20 00 Unit Masonry04 20 00 1-9

DIVISION 05 – METALS

05 12 00 Structural Steel Framing05 12 00 1-9
05 21 00 Steel Joist Framing05 21 00 1-6
05 31 00 Steel Decking05 31 00 1-6
05 40 00 Cold-Formed Metal Framing05 40 00 1-9
05 50 00 Metal Fabrications05 50 00 1-4
05 51 00 Metal Stairs05 51 00 1-5
05 52 13 Pipe and Tube Railings05 52 13 1-3

DIVISION 06 – WOOD, PLASTICS, AND COMPOSITES

06 10 00 Rough Carpentry06 10 00 1-4
06 41 00 Architectural Wood Casework06 41 00 1-5

DIVISION 07 – THERMAL AND MOISTURE PROTECTION

07 11 13 Bituminous Dampproofing07 11 13 1-2
07 14 00 Fluid-Applied Waterproofing07 14 00 1-4
07 21 00 Thermal Insulation07 21 00 1-3
07 21 13 Geofoam Lightweight Fill07 21 13 1-2
07 54 00 Thermoplastic Membrane Roofing07 54 00 1-6
07 61 00 Sheet Metal Roofing07 61 00 1-5
07 62 00 Sheet Metal Flashing and Trim07 62 00 1-3
07 71 23 Manufactured Scuppers, Collection Boxes, Gutters and
Downspouts07 71 23 1-2
07 72 00 Roof Accessories07 72 00 1-3
07 92 00 Joint Sealants07 92 00 1-5

DIVISION 08 OPENINGS

08 06 71	Door Hardware Schedule	08 06 71	1-4
08 11 13	Hollow Metal Doors and Frames	08 11 13	1-4
08 14 16	Flush Wood Doors.....	08 14 16	1-3
08 31 00	Access Doors and Panels.....	08 31 00	1-2
08 33 26	Overhead Coiling Grilles.....	08 33 26	1-3
08 43 13	Aluminum-Framed Storefronts	08 43 13	1-6
08 45 23	Insulated Translucent Fiberglass Sandwich Panel Wall System	08 45 23	1-5
08 51 16	Sliding Aluminum Pass Windows.....	08 51 16	1-2
08 71 00	Door Hardware	08 71 00	1-10
08 80 00	Glazing	08 80 00	1-6

DIVISION 09 FINISHES

09 05 61	Common Work Results for Flooring Preparation	09 05 61	1-4
09 21 16	Gypsum Board Assemblies	09 21 16	1-5
09 30 00	Tiling	09 30 00	1-5
09 51 00	Suspended Acoustical Ceilings	09 51 00	1-4
09 65 00	Resilient Flooring	09 65 00	1-4
09 65 66	Resilient Athletic Flooring	09 65 66	1-6
09 68 13	Tile Carpeting.....	09 68 13	1-3
09 68 16	Walk-Off Entrance System.....	09 68 16	1-3
09 72 10	Custom Digital Wall Coverings	09 72 10	1-3
09 84 00	Acoustical Wall Panels.....	09 84 00	1-3
09 91 13	Exterior Painting.....	09 91 13	1-5
09 91 23	Interior Painting.....	09 91 23	1-5

DIVISION 10 – SPECIALTIES

10 14 19	Dimensional Letter Signage	10 14 19	1-3
10 21 13.19	Solid Plastic Toilet Compartments.....	10 21 13.19	1-3
10 28 00	Toilet and Bath Accessories	10 28 00	1-3
10 44 00	Fire Protection	10 44 00	1-2
10 73 01	Aluminum Canopy	10 73 01	1-3
10 75 00	Flagpoles.....	10 75 00	1-3

DIVISION 11 – EQUIPMENT

11 66 23	Gymnasium Equipment.....	11 66 23	1-5
11 66 53	Divider Curtain.....	11 66 53	1-4

DIVISION 12 – FURNISHINGS

12 21 13	Horizontal Louver Blinds	12 21 13	1-3
12 24 13	Manual Window Shade System.....	12 24 13	1-3
12 36 00	Countertops.....	12 36 00	1-3

DIVISION 13 – SPECIAL CONSTRUCTION (NOT USED)

DIVISION 14 – CONVEYING EQUIPMENT (NOT USED)

DIVISION 21 – FIRE SUPPRESSION

21 05 00	Basic Fire Protection Requirements	21 05 00	1-11
21 05 17	Sleeves and Sleeve Seals for Fire-Suppression Piping.....	21 05 17	1-4
21 05 18	Escutcheons for Fire-Suppression Piping.....	21 05 18	1-3
21 05 23	General-Duty Valves for Fire Protection Piping	21 05 23	1-6
21 05 48	Vibration and Seismic Controls for Fire-Suppression Piping and Equipment.....	21 05 48	1-8
21 05 53	Identification for Fire-Suppression Piping and Equipment.....	21 05 53	1-5
21 11 19	Fire Department Connections.....	21 11 19	1-3
21 13 13	Wet-Pipe Sprinkler Systems.....	21 13 13	1-13

DIVISION 22 - PLUMBING

22 05 00	Basic Plumbing Requirements	22 05 00	1-11
22 05 17	Sleeves and Sleeve Seals for Plumbing Piping	22 05 17	1-3
22 05 18	Escutcheons for Plumbing Piping	22 05 18	1-2
22 05 19	Meters and Gages for Plumbing Piping.....	22 05 19	1-4
22 05 23.12	Ball Valves for Plumbing Piping.....	22 05 23.12	1-5
22 05 23.14	Check Valves for Plumbing Piping	22 05 23.14	1-5
22 05 29	Hangers and Supports for Plumbing Piping and Equipment.....	22 05 29	1-10
22 05 53	Identification for Plumbing Piping and Equipment.....	22 05 53	1-5
22 07 19	Plumbing Piping Insulation	22 07 19	1-14
22 11 16	Domestic Water Piping.....	22 11 16	1-10
22 11 19	Domestic Water Piping Specialties	22 11 19	1-13
22 13 16	Sanitary Waste and Vent Piping.....	22 13 16	1-9
22 13 19	Sanitary Waste Piping Specialties	22 13 19	1-8
22 33 00	Electric, Domestic-Water Heaters	22 33 00	1-6

DIVISION 23 – HEATING, VENTILATING AND AIR CONDITIONING (HVAC)

23 05 00	Basic Mechanical Requirements	23 05 00	1-11
23 01 30.51	HVAC Air Duct Cleaning	23 01 30.51	1-4
23 05 00	Common Work Results for HVAC	23 05 00	1-10

23 05 13	Common Motor Requirements for HVAC Equipment	23 05 13	1-3
23 05 48	Vibration and Seismic Controls for HVAC Piping & Equip.	23 05 48	1-12
23 05 53	Identification for HVAC Piping and Equipment	23 05 53	1-6
23 05 93	Testing, Adjusting and Balancing for HVAC	23 05 93	1-13
23 07 13	Duct Insulation	23 07 13	1-11
23 09 23.07	Temperature Instruments	23 09 23.07	1-12
23 09 23	Direct Digital Control (DDC) System for HVAC	23 09 23	1-83
23 31 13	Metal Ducts	23 31 13	1-12
23 33 00	Air Duct Accessories	23 33 00	1-11
23 34 23	HVAC Power Ventilators	23 34 23	1-7
23 37 13.13	Air Diffusers	23 37 13.13	1-5
23 37 13.23	Air Registers & Grilles	23 37 13.23	1-3
23 74 13	Packaged Rooftop Units / Outdoor Air Handling Units	23 74 13	1-9

DIVISION 26 – ELECTRICAL

26 01 00	Basic Electrical Requirements	26 01 00	1-17
26 05 00	Common Work Results for Electrical	26 05 00	1-25
26 05 19	Low Voltage Electrical Power Conductors and Cables	26 05 19	1-7
26 05 26	Grounding and Bonding for Electrical Systems	26 05 26	1-8
26 05 29	Hanger and Supports for Electrical Systems	26 05 29	1-8
26 05 33	Raceways, Boxes and Fittings for Electrical Systems	26 05 33	1-12
26 05 53	Identification for Electrical Systems	26 05 53	1-8
26 05 90	Electrical Testing	26 05 90	1-3
26 05 95	Service Entrance	26 05 95	1-4
26 09 24	Lighting Control Devices	26 09 24	1-14
26 24 13	Switchboards	26 24 13	1-10
26 24 16	Panelboards	26 24 16	1-10
26 27 26	Wiring Devices	26 27 26	1-6
26 28 13	Fuses	26 28 13	1-3
26 28 16	Disconnect Switches and Enclosed Circuit Breakers	26 28 16	1-8
26 32 13	Engine Generators	26 32 13	1-18
26 36 00	Transfer Switches	26 36 00	1-10
26 51 00	Interior Lighting	26 51 00	1-9
26 56 00	Exterior Lighting	26 56 00	1-11

DIVISION 27 – COMMUNICATIONS

27 05 26	Grounding and Bonding for Communications Systems	27 05 26	1-8
27 05 28	Pathways for Communications Systems	27 05 28	1-10
27 05 36	Cable Trays for Communications Systems	27 05 36	1-6
27 11 00	Communications Equipment Room Fittings	27 11 00	1-5
27 15 00	Communications Horizontal Cabling	27 15 00	1-11
27 51 16	Public Address Systems	27 51 16	1-10

DIVISION 28 – ELECTRONIC SAFETY AND SECURITY

28 05 13	Conductors and Cables for Electronic Safety and Security.....	28 05 13	1-8
28 05 28	Pathways for Electronic Safety and Security	28 05 28	1-8
28 13 00	Access Control.....	28 13 00	1-32
28 31 11	Digital, Addressable Fire-Alarm System	28 31 11	1-15

DIVISION 31 – EARTHWORK

31 00 00	Earthwork	31 00 00	1-6
31 05 13	Soils for Earthwork.....	31 05 13	1-4
31 10 00	Site Clearing	31 10 00	1-6
31 20 00	Earth Moving.....	31 20 00	1-18
31 23 16.13	Trenching.....	31 23 16.13	1-7
31 23 16.26	Rock Removal	31 23 16.26	1-2
31 23 16.29	Unsuitable Soil Removal.....	31 23 16.29	1-2
31 23 19	Dewatering	31 23 16	1-4
31 31 16	Termite Control	31 31 16	1-2
31 37 00	Riprap	31 37 00	1-2

DIVISION 32 – EXTERIOR IMPROVEMENTS

32 11 23	Aggregate Base Course	32 11 23	1-3
32 12 16	Asphalt Paving.....	32 12 16	1-8
32 13 13	Concrete Paving.....	32 13 13	1-21
32 13 73	Concrete Paving Joint Sealants	32 13 73	1-5
32 17 23	Pavement Markings	32 17 23	1-8

DIVISION 33 – UTILITIES

33 05 00	Common Work Results for Utilities.....	33 05 00	1-12
33 05 13	Manholes and Structures	33 05 13	1-4
33 11 13	Public Water Utility Distribution Piping.....	33 11 13	1-6
33 30 00	Sanitary Sewage Utilities	33 30 00	1-8
33 41 00	Storm Utility Drainage Piping.....	33 41 00	1-5

END OF TABLE OF CONTENTS

SECTION 23 74 13

PACKAGED ROOFTOP UNITS / OUTDOOR AIR HANDLING UNITS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

1.2 GENERAL DESCRIPTION

- A. This section includes the design, controls and installation requirements for packaged rooftop units / outdoor air handling units.

1.3 QUALITY ASSURANCE

- A. Unit shall be certified in accordance with UL Standard 1995/CSA C22.2 No. 236, Safety Standard for Heating and Cooling Equipment.
- B. HP-01 HP-04 HP-03 HP-02 Unit and refrigeration system shall comply with ASHRAE 15, Safety Standard for Mechanical Refrigeration.
- C. HP-04 Unit Seasonal Energy Efficiency Ratio (SEER) shall be equal to or greater than that prescribed by ASHRAE 90.1, Energy Efficient Design of New Buildings except Low-Rise Residential Buildings.
- D. HP-01 HP-03 HP-02 Unit Energy Efficiency Ratio (EER) shall be equal to or greater than that prescribed by ASHRAE 90.1, Energy Efficient Design of New Buildings except Low-Rise Residential Buildings.
- E. HP-01 HP-04 HP-03 HP-02 Unit shall be safety certified by ETL and ETL US listed. Unit nameplate shall include the ETL/ETL Canada label.

1.4 SUBMITTALS

- A. Product Data: Literature shall be provided that indicates dimensions, operating and shipping weights, capacities, ratings, fan performance, filter information, factory supplied accessories, electrical characteristics and connection requirements. Installation, Operation, and Maintenance manual with startup requirements shall be provided.
- B. Shop Drawings: Unit drawings shall be provided that indicate assembly, unit dimensions, construction details, clearances and connection details. Computer generated fan curves for each fan shall be submitted with specific design operation point noted. Wiring diagram shall be provided with details for both power and control systems and differentiate between factory installed and field installed wiring.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Unit shall be shipped with doors screwed shut and outside air hood closed to prevent damage during transport and thereafter while in storage awaiting installation.

- B. Follow Installation, Operation, and Maintenance manual instructions for rigging, moving, and unloading the unit at its final location.
- C. Unit shall be stored in a clean, dry place protected from construction traffic in accordance with the Installation, Operation, and Maintenance manual.

1.6 WARRANTY

- A. HP-01 HP-04 HP-03 HP-02 Manufacturer shall provide a limited “parts only” warranty for a period of 12 months from the date of equipment startup. Warranty shall cover material and workmanship that prove defective, within the specified warranty period, provided manufacturer’s written instructions for Installation, Operation, and maintenance have been followed. Warranty excludes parts associated with routine maintenance, such as belts and filters.
- B. Provide an additional five years “parts only” warranty on all compressors.

PART 2 - PRODUCTS

2.1 MANUFACTURER

- A. Products shall be provided by the following manufacturers:
 - 1. AAON
 - 2. Substitute equipment may be considered for approval that includes at a minimum:
 - a. HP-01 HP-04 HP-03 HP-02 Variable capacity compressor with 10-100% capacity control
 - b. Direct drive supply fans
 - c. Double wall cabinet construction
 - d. Insulation with a minimum R-value of 13
 - e. HP-01 HP-04 HP-03 HP-02 Stainless steel drain pans

2.2 ROOFTOP UNITS

- A. General Description
 - 1. HP-01 HP-04 HP-03 HP-02 Packaged rooftop unit shall include compressors, evaporator coils, filters, supply fans, dampers, air-cooled condenser coils, condenser fans, reheat coil, electric heaters, exhaust fans, energy recovery wheels, and unit controls.
 - 2. Unit shall be factory assembled and tested including leak testing of the DX coils, pressure testing of the refrigeration circuit, and run testing of the completed unit. Run test report shall be supplied with the unit in the service compartment’s literature pocket.
 - 3. Unit shall have decals and tags to indicate lifting and rigging, service areas and caution areas for safety and to assist service personnel.
 - 4. Unit components shall be labeled, including refrigeration system components and electrical and controls components.
 - 5. Estimated sound power levels (dB) shall be shown on the unit ratings sheet.
 - 6. Installation, Operation, and Maintenance manual shall be supplied within the unit.
 - 7. Laminated color-coded wiring diagram shall match factory installed wiring and shall be affixed to the interior of the control compartment’s hinged access door.
 - 8. Unit nameplate shall be provided in two locations on the unit, affixed to the exterior

of the unit and affixed to the interior of the control compartment's hinged access door.

B. Construction

1. All cabinet walls, access doors, and roof shall be fabricated of double wall, impact resistant, rigid polyurethane foam panels.
2. Unit insulation shall have a minimum thermal resistance R-value of 13. Foam insulation shall have a minimum density of 2 pounds/cubic foot and shall be tested in accordance with ASTM D1929-11 for a minimum flash ignition temperature of 610°F.
3. Unit construction shall be double wall with G90 galvanized steel on both sides and a thermal break. Double wall construction with a thermal break prevents moisture accumulation on the insulation, provides a cleanable interior, prevents heat transfer through the panel, and prevents exterior condensation on the panel.
4. Unit shall be designed to reduce air leakage and infiltration through the cabinet. Cabinet leakage shall not exceed 1% of total airflow when tested at 3 times the minimum external static pressure provided in AHRI Standard 340/360. Panel deflection shall not exceed L/240 ratio at 125% of design static pressure, at a maximum 8 inches of positive or negative static pressure, to reduce air leakage. Deflection shall be measured at the midpoint of the panel height and width. Continuous sealing shall be included between panels and between access doors and openings to reduce air leakage. Piping and electrical conduit through cabinet panels shall include sealing to reduce air leakage.
5. Unit shall be designed to reduce air leakage and infiltration through the cabinet. Cabinet leakage shall not exceed 1% of total airflow when tested at 3 times the minimum external static pressure provided in AHRI Standard 210/240. Panel deflection shall not exceed L/240 ratio at 125% of design static pressure, at a maximum 8 inches of positive or negative static pressure, to reduce air leakage. Deflection shall be measured at the midpoint of the panel height and width. Continuous sealing shall be included between panels and between access doors and openings to reduce air leakage. Piping and electrical conduit through cabinet panels shall include sealing to reduce air leakage.
6. Roof of the air tunnel shall be sloped to provide complete drainage. Cabinet shall have rain break overhangs above access doors.
7. HP-01 HP-04 HP-03 HP-02 Access to filters, dampers, cooling coils, reheat coil, heaters, energy recovery wheels, compressors, and electrical and controls components shall be through hinged access doors with quarter turn, zinc cast, lockable handles. Full-length stainless-steel piano hinges shall be included on the doors.
8. Exterior paint finish shall be capable of withstanding at least 2,500 hours, with no visible corrosive effects, when tested in a salt spray and fog atmosphere in accordance with ASTM B 117-95 test procedure.
9. Units with cooling coils shall include double sloped 304 stainless steel drain pans.
10. HP-04 HP-03 HP-02 Unit shall be provided with base discharge and return air openings. All openings through the base pan of the unit shall have upturned flanges of at least 1/2 inch in height around the opening.
11. HP-01 Unit shall be provided with horizontal discharge and horizontal return air openings. All openings through the base pan of the unit shall have upturned flanges of at least 1/2 inch in height around the opening.
12. Unit shall include lifting lugs on the top of the unit.

13. HP-02 Unit base shall be fabricated of 1-inch thick double wall, impact resistant, rigid polyurethane foam panels.
- C. Electrical
1. HP-01 HP-04 HP-03 HP-02 Unit shall have a 5kAIC SCCR.
 2. HP-01 HP-04 HP-03 HP-02 Unit shall be provided with factory installed and factory wired, non-fused disconnect switch.
 3. HP-01 HP-04 HP-03 HP-02 Unit shall be provided with a factory installed and factory wired 115V, 12-amp GFI outlet disconnect switch in the unit control panel.
 4. HP-01 HP-04 HP-03 HP-02 Unit shall be provided with phase and brown out protection which shuts down all motors in the unit if the electrical phases are more than 10% out of balance on voltage, the voltage is more than 10% under design voltage or on phase reversal.
- D. Supply Fans
1. Unit shall include direct drive, unhooded, backward curved, plenum supply fans.
 2. Blowers and motors shall be dynamically balance and mounted on rubber isolators.
 3. HP-01 HP-04 HP-03 HP-02 Motors shall be premium efficiency ODP with ball bearings rated for 200,000 hours service with external lubrication points.
 4. HP-04 HP-03 HP-02 Variable frequency drives shall be factory wired and mounted in the unit. Fan motors shall be premium efficiency.
- E. HP-02 Exhaust Fans
1. Exhaust dampers shall be sized for 100% relief.
 2. Fans and motors shall be dynamically balanced.
 3. HP-02 Motors shall be premium efficiency ODP with ball bearings rated for 200,000 hours service with external lubrication points.
 4. Access to exhaust fans shall be through double wall, hinged access doors with quarter turn lockable handles.
 5. HP-02 Unit shall include belt driven, unhooded, backward curved, plenum exhaust fans.
 6. HP-02 Variable frequency drives shall be factory wired and mounted in the unit. Fan motors shall be premium efficiency.
- F. HP-01 HP-04 HP-03 HP-02 Cooling Coils
1. HP-01 HP-04 HP-03 HP-02 Evaporator Coils
 - a. HP-01 HP-04 HP-03 HP-02 Coils shall be designed for use with R-410A refrigerant and constructed of copper tubes with aluminum fins mechanically bonded to the tubes and galvanized steel end casings. Fin design shall be sine wave rippled.
 - b. HP-04 HP-03 Coils shall be standard capacity.
 - c. HP-01 HP-02 Coils shall have interlaced circuitry and shall be standard capacity.
 - d. Coils shall be hydrogen or helium leak tested.
 - e. Coils shall be furnished with factory installed expansion valves.
- G. HP-01 HP-04 HP-03 HP-02 Refrigeration System
1. HP-01 HP-04 HP-03 HP-02 Unit shall be factory charged with R-410A refrigerant.
 2. HP-01 HP-04 HP-03 HP-02 Compressors shall be scroll type with thermal overload protection and carry a 5-year non-prorated warranty, from the date of original equipment shipment from the factory.

3. Compressors shall be mounted in an isolated service compartment which can be accessed without affecting unit operation. Lockable hinged compressor access doors shall be fabricated of double wall, rigid polyurethane foam injected panels to prevent the transmission of noise outside the cabinet.
4. Compressors shall be isolated from the base pan with the compressor manufacturer's recommended rubber vibration isolators, to reduce any transmission of noise from the compressors into the building area.
5. Each refrigeration circuit shall be equipped with expansion valve type refrigerant flow control.
6. Each refrigeration circuit shall be equipped with automatic reset low pressure and manual reset high pressure refrigerant safety controls, service fittings on both the high pressure and low-pressure sides and a factory installed replaceable core liquid line filter driers.
7. HP-04 HP-03 Unit shall include a variable capacity scroll compressor on the refrigeration circuit which shall be capable of modulation from 10-100% of its capacity.
8. HP-01 Unit shall include a variable capacity scroll compressor on the lead refrigeration circuit which shall be capable of modulation from 10-100% of its capacity.
9. HP-02 Unit shall include a variable capacity scroll compressor on all refrigeration circuits which shall be capable of modulation from 10-100% of its capacity.
10. HP-04 HP-03 Refrigeration circuit shall be provided with hot gas reheat coil, modulating valves, electronic controller, supply air temperature sensor and a control signal terminal which allow the unit to have a dehumidification mode of operation, which includes supply air temperature control to prevent supply air temperature swings and overcooling of the space.
11. HP-01 Lead refrigeration circuit shall be provided with hot gas reheat coil, modulating valves, electronic controller, supply air temperature sensor and a control signal terminal which allow the unit to have a dehumidification mode of operation, which includes supply air temperature control to prevent supply air temperature swings and overcooling of the space.
12. HP-02 Lead refrigeration circuits shall be provided with hot gas reheat coil, modulating valves, electronic controller, supply air temperature sensor and a control signal terminal which allow the unit to have a dehumidification mode of operation, which includes supply air temperature control to prevent supply air temperature swings and overcooling of the space.
13. HP-04 HP-03 Unit shall be configured as an air-source heat pump. Refrigeration circuit shall be equipped with a factory installed liquid line filter drier with check valve, reversing valve, accumulator, and expansion valves on both the indoor and outdoor coils. Reversing valve shall energize during the heat pump cooling mode of operation.
14. HP-01 HP-02 Unit shall be configured as an air-source heat pump. Each refrigeration circuit shall be equipped with a factory installed liquid line filter drier with check valve, reversing valve, accumulator, and expansion valves on both the indoor and outdoor coils. Reversing valve shall energize during the heat pump cooling mode of operation.
15. HP-01 Lead refrigeration circuit shall be equipped with flooded condenser low ambient head pressure control to allow operation down to 0°F. Option includes an adjustable compressor lockout.

- H. HP-01 HP-04 HP-03 HP-02 Condensers
1. HP-01 HP-04 HP-03 HP-02 Air-Cooled Condenser
 - a. Condenser fans shall be a vertical discharge, axial flow, direct drive fans.
 - b. HP-01 HP-04 HP-03 HP-02 Heat pump outdoor coil shall be constructed of copper tubes with aluminum fins mechanically bonded to the tubes and aluminum end casings. Fin design shall be sine wave rippled.
 - c. Coils shall be designed for a minimum of 10°F of refrigerant sub-cooling.
 - d. Coils shall be hydrogen or helium leak tested.
 - e. HP-01 HP-04 Condenser fans shall be high efficiency electrically commutated motor driven with factory installed head pressure control module. Condenser airflow shall continuously modulate based on head pressure and cooling operation shall be allowed down to 35°F with adjustable compressor lockout.
 - f. HP-01 HP-03 HP-02 Condenser fans shall be VFD driven variable speed for condenser head pressure control. Factory provided and factory programmed VFDs shall continuously modulate the fan air flow to maintain head pressure at acceptable levels. Cooling operation shall be allowed down to 35°F with adjustable compressor lockout.
- I. HP-01 HP-04 HP-03 HP-02 Electric Heating
1. Unit shall include an electric heater consisting of electric heating coils, fuses and a high temperature limit switch, with capacities as shown on the plans.
 2. Electric heating coils shall be located in the reheat position downstream of the cooling coil.
 3. HP-01 Electric heater shall have full modulation capacity controlled by an SCR (Silicon Controlled Rectifier). Supply air temperature sensor shall be factory provided and field installed in the supply air ductwork. A 0-10 VDC terminal block shall be factory provided for external control.
 4. HP-01 HP-04 HP-03 HP-02 Electric heater shall have full modulation capacity controlled by an SCR (Silicon Controlled Rectifier). A 0-10 VDC heating control signal shall be field provided to control the amount of heating.
 5. HP-01 HP-04 HP-03 HP-02 Auxiliary electric heating capacity shall be sized to meet heating leaving air temperature setpoint when heat pump heating is in operation. Auxiliary heating capacity shall be available for operation when heat pump heating is in operation. Unit shall include 1 stage of auxiliary electric heating capacity. Heat Pump - Auxiliary Heat Sizing
 6. HP-01 HP-04 HP-03 HP-02 Emergency electric heating capacity shall be sized by determining the maximum electric heating capacity not to exceed the amp draw of all compressors and adding that electric heating capacity to the auxiliary electric heating capacity. Auxiliary electric heating capacity shall be sized to meet heating leaving air temperature setpoint when heat pump heating is in operation. Unit shall include 1 stage of auxiliary electric heating capacity. Heat Pump - MCA Limited Heat Sizing
 7. HP-01 HP-04 HP-03 HP-02 Emergency electric heating capacity shall be sized to meet heating leaving air temperature setpoint when heat pump heating is not in operation. Auxiliary electric heating capacity shall be sized to meet heating leaving air temperature setpoint when heat pump heating is in operation. Unit shall include 1 stage of auxiliary electric heating capacity. Heat Pump - Emergency Heat Sizing
 8. HP-02 Outdoor Airflow Monitoring

- a. Unit shall include outside airflow measuring station and airflow signal processor that communicates directly with the factory provided control systems or can also be used with customer provided controls with a 0-10 VDC output signal. LonTalk and BACnet may also be available for some applications. Monitoring size is dependent on the cfm.
- J. Filters
1. HP-01 HP-04 HP-03 Unit shall include 2-inch-thick, pleated panel filters with an ASHRAE MERV rating of 8, upstream of the cooling coil.
 2. HP-01 Unit shall include 2-inch-thick, pleated panel filters with an ASHRAE MERV rating of 8, upstream of the cooling coil.
 3. HP-02 Unit shall include 4-inch-thick, pleated panel filters with an ASHRAE MERV rating of 13, upstream of the cooling coil. Unit shall also include 2-inch-thick, pleated panel pre filters with an ASHRAE MERV rating of 8, upstream of the 4-inch standard filters.
- K. HP-01 HP-04 HP-03 HP-02 Outside Air/Economizer
1. HP-01 HP-04 HP-03 HP-02 Unit shall include 0-100% economizer consisting of a motor operated outside air damper and return air damper assembly constructed of extruded aluminum, hollow core, airfoil blades with rubber edge seals and aluminum end seals. Damper blades shall be gear driven and designed to have no more than 20 cfm of leakage per sq ft. at 4 in. w.g. air pressure differential across the damper. Low leakage dampers shall be Class 2 AMCA certified, in accordance with AMCA Standard 511. Damper assembly shall be controlled by spring return enthalpy activated fully modulating actuator. Unit shall include outside air opening bird screen, outside air hood, and barometric relief dampers.
- L. HP-02 Energy Recovery
1. HP-02 Unit shall contain a factory mounted and tested energy recovery wheels. The energy recovery wheels shall be mounted in a rigid frame containing the wheel drive motor, drive belt, wheel seals and bearings. Frame shall slide out for service and removal from the cabinet.
 2. The energy recovery component shall incorporate a rotary wheel in an insulated cassette frame complete with seals, drive motor and drive belt.
 3. HP-02 Wheels shall be wound continuously with one flat and one structured layer in an ideal parallel plate geometry providing laminar flow and minimum pressure drop-to-efficiency ratios. The layers shall be effectively captured in stainless steel wheel frames or aluminum and stainless-steel segment frames that provide a rigid and self-supporting matrix.
 4. HP-02 Wheels shall be provided with removable energy transfer matrix. Wheel frame construction shall be a welded hub, spoke and rim assembly of stainless, plated and/or coated steel and shall be self-supporting without matrix segments in place. Segments shall be removable without the use of tools to facilitate maintenance and cleaning. Wheel bearings shall be selected to provide an L-10 life in excess of 400,000 hours. Rim shall be continuous rolled stainless steel and the wheel shall be connected to the shaft by means of taper locks.
 5. All diameter and perimeter seals shall be provided as part of the cassette assembly and shall be factory set. Drive belts of stretch urethane shall be provided for wheel rim drive without the need for external tensioners or adjustment.
 6. The energy recovery cassette shall be an Underwriters Laboratories Recognized Component for electrical and fire safety. The wheel drive motor shall be an

Underwriters Laboratory Recognized Component and shall be mounted in the cassette frame and supplied with a service connector or junction box. Thermal performance shall be certified by the manufacturer in accordance with ASHRAE Standard 84, Method of Testing Air-to-Air Heat Exchangers and AHRI Standard 1060, Rating Air-to-Air Energy Recovery Ventilation Equipment. Cassettes shall be listed in the AHRI Certified Products.

7. Energy recovery wheel cassette shall carry a 5-year non-prorated warranty, from the date of original equipment shipment from the factory. The first 12 months from the date of equipment startup, or 18 months from the date of original equipment shipment from the factory, whichever is less, shall be covered under the standard AAON limited parts warranty. The remaining period of the warranty shall be covered by Airxchange. The 5-year warranty applies to all parts and components of the cassette, with the exception of the motor, which shall carry an 18-month warranty. Warranty shall cover material and workmanship that prove defective, within the specified warranty period, provided the Airxchange written instructions for Installation, Operation, and Maintenance have been followed. Warranty excludes parts associated with routine maintenance, such as belts. Refer to the Airxchange Energy Recovery Cassette Limited Warranty Certificate.
8. HP-02 Unit shall include 2-inch-thick, pleated panel outside air filters with an ASHRAE MERV rating of 8, upstream of the wheels.
9. HP-02 Hinged service access doors shall allow access to the wheels.
10. HP-02 Total energy recovery wheels shall be coated with silica gel desiccant permanently bonded by a process without the use of binders or adhesives, which may degrade desiccant performance. The substrate shall be lightweight polymer and shall not degrade nor require additional coatings for application in marine or coastal environments. Coated segments shall be washable with detergent or alkaline coil cleaner and water. Desiccant shall not dissolve nor deliquesce in the presence of water or high humidity.

M. Controls

1. HP-01 HP-04 HP-03 HP-02 Factory Installed and Factory Provided Controller
 - a. Unit controller shall be capable of controlling all features and options of the unit. Controller shall be factory installed in the unit controls compartment and factory tested. Controller shall be capable of standalone operation with unit configuration, setpoint adjustment, sensor status viewing, unit alarm viewing, and occupancy scheduling available without dependence on a building management system.
 - b. Controller shall have an onboard clock and calendar functions that allow for occupancy scheduling.
 - c. Controller shall include non-volatile memory to retain all programmed values without the use of a battery, in the event of a power failure.
 - d. HP-01 HP-04 HP-03 HP-02 Variable Air Volume Controller
2. HP-01 HP-04 HP-03 HP-02 Unit shall utilize a variable capacity compressor system and a variable speed supply fan system to modulate cooling and airflow as required to meet space temperature cooling loads and to save operating energy. Supply fan speed shall modulate based on supply air duct static pressure. Cooling capacity shall modulate based on supply air temperature.
3. HP-01 HP-04 HP-03 HP-02 With modulating hot gas reheat, unit shall modulate cooling and hot gas reheat as efficiently as possible, to meet space humidity loads and prevent supply air temperature swings and overcooling of the space.

4. HP-01 HP-04 HP-03 HP-02 Unit shall modulate heating with constant airflow to meet space temperature heating loads. Modulating heating capacity shall modulate based on supply air temperature.
 - a. HP-02 Unit configuration, setpoint adjustment, sensor status viewing, unit alarm viewing, and occupancy scheduling shall be accomplished with connection to interface module with LCD screen and input keypad, interface module with touch screen, or with connection to PC with free configuration software. Controller shall be capable of connection with other factory installed and factory provided unit controllers with individual unit configuration, setpoint adjustment, sensor status viewing, and occupancy scheduling available from a single unit. Connection between unit controllers shall be with a modular cable. Controller shall be capable of communicating and integrating with a LonWorks or BACnet network.
 - b. HP-04 HP-03 Unit configuration, setpoint adjustment, sensor status viewing, unit alarm viewing, and occupancy scheduling shall be accomplished with a touchscreen controller interface. Controller shall be capable of communicating and integrating with a BACnet MS/TP or Modbus RTU network. AAON Touchscreen Controller
- N. HP-01 Accessories
 1. HP-01 Unit shall be provided with a safety shutdown terminal block for field installation of a smoke detector which shuts off the unit's control circuit.
 2. HP-01 HP-04 HP-03 HP-02 Unit shall be provided with a high condensate level switch that shuts down the unit when a high-water level is detected in the drain pan.

PART 3 - EXECUTION

3.1 INSTALLATION, OPERATION, AND MAINTENANCE

- A. Installation, Operation, and Maintenance manual shall be supplied with the unit.
- B. Installing contractor shall install unit, including field installed components, in accordance with Installation, Operation, and Maintenance manual instructions.
- C. Start up and maintenance requirements shall be complied with to ensure safe and correct operation of the unit.

END OF SECTION 23 74 13